



Powering your way to safety  
Since 1972



## ABC Stored Pressure Type Fire Extinguisher

FIRE EXTINGUISHER CAPACITY	1kg.	2kg.	3kg.	4kg.	6kg.	9kg.
MINIMUM PERIOD FOR WHICH THROW OF JET MAINTAINED	8 sec	8 sec	16 sec	16 sec	20 sec	25 sec
MINIMUM PERIOD TO DISCHARGE ATLEAST 90% OF CONTESTS	12 sec	16 sec	20 sec	20 sec	25 sec	30 sec
RANGE OF JET	2 mtr.	3 mtr.	4 mtr.	4 mtr.	6 mtr.	7 mtr.
EMPTY. WT. (APPROX)	1kg.	2.3kg.	2.66kg.	2.75kg.	3.3kg.	5.35kg.
FULL WT. (APPROX)	2kg.	3.3kg.	5.66kg.	6.75kg.	9.3kg.	14.35kg.
FIRE RATING	8B	1A,8B	1A,13B	2A,34B	3A,21B	3A,34B
WORKING PRESSURE	15 KGF/CM <sup>2</sup>	15 KGF/CM <sup>2</sup>	15 KGF/CM <sup>2</sup>	15 KGF/CM <sup>2</sup>	15 KGF/CM <sup>2</sup>	15 KGF/CM <sup>2</sup>
HYDRO PRESSURE	35 KGF/CM <sup>2</sup>	35 KGF/CM <sup>2</sup>	35 KGF/CM <sup>2</sup>	35 KGF/CM <sup>2</sup>	35 KGF/CM <sup>2</sup>	35 KGF/CM <sup>2</sup>
BRUSTING PRESSURE	55 KGF/CM <sup>2</sup>	55 KGF/CM <sup>2</sup>	55 KGF/CM <sup>2</sup>	55 KGF/CM <sup>2</sup>	55 KGF/CM <sup>2</sup>	55 KGF/CM <sup>2</sup>

IS:15683

## ABC / BC Squeeze Grip Cartridge Type Fire Extinguisher



FIRE EXTINGUISHER CAPACITY	6kg. ABC	9kg. ABC	6kg. BC	9kg. BC
MINIMUM PERIOD FOR WHICH THROW OF JET MAINTAINED	20 sec	25 sec	20 sec	25 sec
MINIMUM PERIOD TO DISCHARGE ATLEAST 90% OF CONTESTS	25 sec	30 sec	25 sec	30 sec
RANGE OF JET	4 mtr.	6 mtr.	4 mtr.	6 mtr.
EMPTY. WT. (APPROX)	5.2kg.	7.05kg.	5.2kg.	7.05kg.
FULL WT. (APPROX)	11.2kg.	16.05kg.	11.2kg.	16.05kg.
FIRE RATING	3A,34B	4A,34B	34B	34B
WORKING PRESSURE	15 KGF/CM <sup>2</sup>	15 KGF/CM <sup>2</sup>	15 KGF/CM <sup>2</sup>	15 KGF/CM <sup>2</sup>
HYDRO PRESSURE	35 KGF/CM <sup>2</sup>	35 KGF/CM <sup>2</sup>	35 KGF/CM <sup>2</sup>	35 KGF/CM <sup>2</sup>
BRUSTING PRESSURE	55 KGF/CM <sup>2</sup>	55 KGF/CM <sup>2</sup>	55 KGF/CM <sup>2</sup>	55 KGF/CM <sup>2</sup>

IS:15683

Higher Fire rated Extinguishers Available

Register Office: **SAFEX FIRE SERVICES LTD.**

A-202, Dhanraj Industrial Estate, Dhanraj Mill Compound, S. J. Road, Lower Parel (w), Post Box No. 6314, MUMBAI 400 013. Telephone: +91 22 2493 8108/29. Fax: +91 22 2495 0224. Email: ho@safexfire.com Website:www.safexfire.com

Branch Offices: • **Ahmedabad:** B/16, Hemkoot Commercial Complex, Behind LIC Building, Ashram Road, Ahmedabad - 380 009. Tel: 079 2658 0963 Email: ahmedabad@safexfire.com

• **Baroda:** 57 Sardar Nagar, Near Sardar Nagar Post Office, Nizampura, Baroda - 390 002. Telefax: 0265 2793962

• **Chennai:** 17, Ormes Road, Kilauk, Chennai - 600 010. Tel.: 2641 1855 Fax: 044-2642 7580 Email: chennai@safexfire.com

• **Secundarabad:** D.No. 5-2-307-309, 43, Hyderbasti, R.P. Road, Secundarabad - 500 003. Tel.: 2754 3211, 2754 0884 Fax: 040-2754 3072 Email: secunderabad@safexfire.com

• **Bangalore:** 127/1 1st Main Road, 3rd Stage, 4th Block, Sharada Colony, Bhsaveswara Nagar, Bangalore - 560 079. Tel.: 2328 7779 Fax: 080-2328 7809 Email: bangalore@safexfire.com

• **Kolkata:** M/s. Safety Equipments Mktg Agency, 4-K, Radhanath Chowdhury Road, Kolkata - 700 015. Tel.: 2329 7016, 2329 3825 Fax: 033-2329 3825

• **New Delhi:** D14/A6, Janak Puri, Opp. Institutional Area, New Delhi - 110 058. Tel: 2852 5364 Fax: 55639699 Email: newdelhi@safexfire.com

Works: Plot No. 13, Village Mahim, Taluka Palghar, Opp. BIDCO, Dist.: Thane-401 402. Tel.: (02525) 252 686, 251 482. Fax: (02525) 251 625. Email: nandan.safex@gmail.com



## Water / Foam Store Pressure Type Fire Extinguisher

FIRE EXTINGUISHER CAPACITY	9ltr. (Water)	9ltr. (Foam)
MINIMUM PERIOD FOR WHICH THROW OF JET MAINTAINED	100 sec	35 sec
MINIMUM PERIOD TO DISCHARGE ATLEAST 90% OF CONTESTS	120 sec	60 sec
RANGE OF JET	6 mtr.	6 mtr.
EMPTY. WT. (APPROX)	5.35kg.	5.35kg.
FULL WT. (APPROX)	14.35kg.	14.35kg.
FIRE RATING	3A	3A,21B
WORKING PRESSURE	15 KGF/CM <sup>2</sup>	15 KGF/CM <sup>2</sup>
HYDRO PRESSURE	35 KGF/CM <sup>2</sup>	35 KGF/CM <sup>2</sup>
BRUSTING PRESSURE	55 KGF/CM <sup>2</sup>	55 KGF/CM <sup>2</sup>

 IS:15683

## Water / Foam Squeeze Grip Cartridge Type Fire Extinguisher



FIRE EXTINGUISHER CAPACITY	9ltr. (Water)	9ltr. (Foam)
MINIMUM PERIOD FOR WHICH THROW OF JET MAINTAINED	100 sec	35 sec
MINIMUM PERIOD TO DISCHARGE ATLEAST 90% OF CONTESTS	120 sec	60 sec
RANGE OF JET	6 mtr.	6 mtr.
EMPTY. WT. (APPROX)	7kg.	7kg.
FULL WT. (APPROX)	16kg.	16kg.
FIRE RATING	3A	3A,34B
WORKING PRESSURE	15 KGF/CM <sup>2</sup>	15 KGF/CM <sup>2</sup>
HYDRO PRESSURE	35 KGF/CM <sup>2</sup>	35 KGF/CM <sup>2</sup>
BRUSTING PRESSURE	55 KGF/CM <sup>2</sup>	55 KGF/CM <sup>2</sup>

 IS:15683

★ Higher Fire rated Extinguishers Available

Approvals and Accreditation:



AN ISO 9001:2000 COMPANY